

CR-N500 REMOTE CAMERA

VIVID 4K AT YOUR FINGERTIPS



Canon's CR-N500 4K UHD PTZ camera produces exceptional image quality and is equipped with powerful features and functions to be utilized in many industries including House of Worship, Education, Broadcast, Corporate, Events and more.



**High Quality 4K 30P
and FHD 60P Video Output**

**Smooth & Responsive
Pan and Tilt Control**

**Seamless Integration into
Canon Imaging Workflow**

**Easy Integration
into IP Systems**

**Various Interfaces Supported
for Multiple Environments**

One-Person Operation

Three Year Warranty

The CR-N500 produces incredible image quality with the combination of a 1" 4K CMOS sensor, DIGIC DV 6 image processor and 15x optical zoom 4K UHD lens. These core components provide the image-processing power and speed that enables 4K UHD video acquisition, image stabilization and precise Dual Pixel CMOS AF. On-air pan and tilt movement is possible thanks to the smooth and responsive pan and tilt mechanism equipped with the CR-N500.

The CR-N500 camera supports Canon's new XC Protocol as well as RTMP, NDI®|HX Live Video Production Protocol, Standard (VISCA) Protocol and more. The CR-N500 can be controlled remotely by IP, Serial, IR or wirelessly via Wi-Fi.

HIGH QUALITY 4K 30P AND FHD 60P VIDEO OUTPUT

The CR-N500 features a Canon 1.0-inch 4K CMOS image sensor capable of 4K UHD video capture at 30P and up to 60P in Full HD, making the CR-N500 PTZ camera ideal for the remote and unobtrusive capture of professional productions.

The CR-N500's 1.0-inch sensor allows for larger photosites, resulting in stunning images with less noise in low-light situations. The larger sensor also exhibits a shallow depth of field at large apertures, producing blurred backgrounds in images, while Canon's DPAF keeps subjects in sharp focus. A nine-bladed iris also helps to produce beautiful and natural bokeh. The CR-N500's DIGIC DV 6 image processor drives the high sensitivity (1.5 lux*) and low noise performance of the camera, yielding amazing imagery in a variety of shooting conditions.

*When camera set to: (3840 × 2160 : shutter speed 1/30 sec., Frame Rate 29.97P, Gain 33.0 dB).



SMOOTH AND RESPONSIVE PAN AND TILT CONTROL

The CR-N500 is equipped with the PT drive mechanism that can change the pan/tilt speed in incremental steps. This allows the operator to set the speed to desired preference to allow for smooth PT movement. The CR-N500 exhibits a variable Pan and Tilt speed of 0.1° - 100°/second.

CR-N500

REMOTE CAMERA



SPECIFICATION	PARAMETER
COLOR	Satin Black / Titanium White
IMAGE SENSOR	Type 1.0 (1.0 in.) single-plate CMOS sensor Total pixels: approx. 13.40 megapixels Effective pixels: approx. 8.29 megapixels (3840 x 2160)
LENS	f=8.3 – 124.5 mm, F/2.8 – 4.5, 15x optical zoom, 9-bladed iris diaphragm 35mm equivalent focal length: approx. 25.5 (W) – 382.5 mm (T)
ZOOM	Optical: 15x Digital: 20x
LENS CONFIGURATION	18 elements in 14 groups (including 2 aspheric elements)
MINIMUM FOCUSING DISTANCE	1 cm (0.39 in.) at full wide angle, 60 cm (2.0 ft.) throughout the zoom range
ANGLE OF VIEW	Horizontal: 73.0 (W) – 5.7° (T) Vertical: 45.2° (W) – 3.2° (T)
SHUTTER SPEED	1/3 – 1/2000 sec. (specific values depend on the frame frequency)
IRIS	Manual/Automatic aperture
GAIN	-6.0 db ~ 33.0 db
ND FILTER	Built-in (Off, 1/4, 1/16, 1/64), motor operated
WHITE BALANCE	AUTO (AWB), Set A, Set B, preset settings (daylight: 5,600 K*, tungsten lamp: 3,200 K*), color temperature setting (2,000 K – 15,000 K), Manual <i>*Color temperatures are given for reference purposes only.</i>
FOCUS	Focus mode: Manual, AF-boosted MF, Continuous AF, Face AF, Tracking AF type: Dual Pixel CMOS AF, Contrast AF
GAMMA	Normal1 (Standard), Normal2 (x4.0), Normal3 (BT.709), Normal4 (x5.0), Wide DR, Canon Log 3
IMAGE STABILIZER	Optical-shift
MIN. SUBJECT ILLUMINATION	3840 x 2160: Approx. 1.5 lux (shutter speed 1/30 sec., frame frequency 2997P, Gain 33.0 dB) 1920 x 1080: Approx. 3 lux (shutter speed 1/60 sec., frame frequency 5994P, Gain 33.0 dB)
PAN AND TILT	Pan operation range: Horizontal ±170° Pan operation speed: 0.1° – 100°/sec. Tilt operation range: Vertical -30° – +90° Tilt operation speed: 0.1° – 100°/sec.

SPECIFICATION	PARAMETER
VIDEO OUTPUT FORMAT	SDI 1920 x 1080: 5994P/5994i, 50.00P/50.00i/25.00P, 2997P/23.98P (4:2:2 10 bit) 1280 x 720: 5994P, 50.00P (4:2:2 10 bit) <i>*Same video format required for SDI and HDMI (cannot select different formats for SDI and HDMI)</i> <i>*When 3840 x 2160 is selected for HDMI, video will not be outputted to SDI</i>
	HDMI 3840 x 2160: 2997P, 25.00P, 23.98P (4:2:2 10 bit) 1920 x 1080: 5994P/5994i, 50.00P/50.00i/25.00P, 2997P/23.98P (4:2:2 10 bit) 1280 x 720: 5994P, 50.00P (4:2:2 10 bit) <i>*Same video format required for SDI and HDMI (cannot select different formats for SDI and HDMI)</i> <i>*When 3840 x 2160 is selected for HDMI, video will not be outputted to SDI.</i>
	IP 3840 x 2160: 2997 fps, 14.99 fps, 5.00 fps (4:2:0 8 bit) 1920 x 1080: 5994 fps, 2997 fps, 14.99 fps, 5.00 fps (4:2:0 8 bit) 1280 x 720: 5994 fps, 2997 fps, 14.99 fps, 5.00 fps (4:2:0 8 bit) 640 x 360: 5994 fps, 2997 fps, 14.99 fps, 5.00 fps (4:2:0 8 bit) <i>*If 5994/50.00 Hz is selected for the frame frequency, the 3840 x 2160 format cannot be selected.</i> <i>*A frame rate that exceeds the frame frequency cannot be selected.</i> <i>*JPEG has one pattern fixed depending on the frame frequency (format is fixed and cannot be selected)</i> Resolution: 1280 x 720 When frame frequency is 5994/50.00 Hz: 14.99 fps, when frame frequency is 23.98 Hz: 11.99 fps, when frame frequency is 2997/25.00 Hz: 12.50 fps
	SUPPORTED VIDEO AND CONTROL PROTOCOLS Protocol: XC Protocol, RTSP/RTP, NDI [®] HX, RTMP/RTMPS, Standard (VISCAN) Communication (Serial), Standard (VISCAN) Communication (IP)
NUMBER OF PRESETS	Max. 100 (including home position)
INTERFACE	COMMUNICATION CONTROL LAN, Wi-Fi, Serial, IR
	NETWORK TERMINAL LAN x 1, RJ45, 1000Base-T
	3G-SDI OUT TERMINAL BNC jack (output only) x 1, 0.8 Vp-p/75 Ω, unbalanced SMPTE 424, SMPTE 425, SMPTE ST 299-2 compliant Embedded audio, Time code (VITC/LTC)
	GEN-LOCK TERMINAL BNC jack x 1, 1.0 Vp-p/75 Ω, input only
	HDMI OUT TERMINAL HDMI connector x 1, output only
	RS-422 TERMINAL RJ45 connector x 1
	INPUT 1 / INPUT 2 XLR TERMINALS INPUT (3-pin jack) (pin1: shield, pin2: hot, pin3: cold), 2 sets, balanced Sensitivity (MIC): -60 dBu (Manual volume center, full scale -18 dB)/600 Ω/Att.: 20 dB Sensitivity (LINE): +4 dBu (Manual volume center, full scale -18 dB)/1 kΩ or more Supply Voltage: 48 V DC (Bias resistance: 6.8 kΩ)
	MIC TERMINAL φ3.5 mm stereo mini jack (unbalanced, plug-in power supported) Sensitivity (MIC): -72 dBV (Manual volume center, full scale -18 dB)/1 kΩ or more/Att.: 20 dB Sensitivity (LINE): -10 dBV (Manual volume center, full scale -18 dB)/1 kΩ or more Supply Voltage: 2.4 V DC (Bias resistance: 2.2 kΩ)
	USB TERMINAL Type-A (USB 2.0) x 1 (service use only)
	MEDIA SLOT microSD card slot x 1, future expansion, recording unavailable
OTHER	OPERATING ENVIRONMENT Temperature: 0°C – +40°C (+32°F – +104°F) Humidity: 10% – 90% (without condensation)
	STORAGE ENVIRONMENT Temperature: 0°C – +40°C (+32°F – +104°F) Humidity: 10% – 90% (without condensation)
	POWER SUPPLY PoE: PoE+ power supply via LAN connector (IEEE802.3at compliant) – PoE cannot be used External power source: 24 V DC (using included AC adaptor)
	POWER CONSUMPTION PoE+ Input: Approx. 19.6 W* max. (body only) DC Input: Approx. 18.6 W max. (body only) <i>*Class 4 (25.5 W required) for power supply devices</i>
	DIMENSIONS (W X H X D) Approx. 7.87 x 10.59 x 8.19 in. (200 x 269 x 208 mm) (excluding protrusions)
	WEIGHT Approx. 904 lb. (4.1 kg) (body only)
SUPPORTED CONTROLLERS Hardware: RC-IP100 Software: Remote Camera Control Application	


RC-IP100 REMOTE CAMERA CONTROLLER



Canon's RC-IP100 Remote Camera Controller provides IP control for up to 99 supported Canon cameras. An additional Canon camera can be controlled through the serial port. The controller is equipped with a 7" interactive touch screen and a joystick in order to pan, tilt, zoom and change camera function settings remotely. The smooth precision of the joystick allows operators to capture on-air movements with confidence.

RC-IP100 Remote Camera Controller sold separately.

For more info: pro.usa.canon.com



Specifications and availability subject to change without notice. Products not shown to scale. Weight and dimensions are approximate. Product shown with optional accessories. Not responsible for typographical errors.
© 2021 Canon U.S.A., Inc. All rights reserved. Canon and EOS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other product names, brand names and logos are trademarks or service marks of their respective owners.
NDI[®] is a registered trademark of NewTek, Inc.
Canon makes no representations or warranties with respect to any third party accessory or product mentioned herein. Use of genuine Canon accessories is recommended; these products are designed to perform optimally when used with genuine Canon accessories.